



SINGLE-SCREW EXTRUDER



- Extruder for rubber extrusion
- Screw made of steel with hard chrome plating
- Smooth running
- Easy to control
- High output
- Easy for maintenance
- Long service life



Model	SE-D40L20	SE-D50L20
Extruder Type	Rubber – Cold Feeding	Rubber – Cold Feeding
Screw Diameter (mm)	40	50
Screw Length/Diameter (L/D)	20	20
Screw Compression Ratio	3:1	3:1
Adjustable Screw Speed (rpm)	0 – 70 Digital Display	0 – 70 Digital Display
Max. Barrel and Die Temp. (°C)	150	150
Heating / Cooling Barrel Zones	3 Electrical Heating / Water Cooling	
Die	Round / Slit / Annular / Others Electrical Heating	
Motor Power (kW)	3.7 with Overload Protection	5.5 with Overload Protection
Power Supply	3 Phase / 380 V / 50 Hz	

Contact us for more information about CT products and services. We are keen on working with you:

CHAREON TUT CO., LTD.

189 Moo 1 Theparak Road, Bangsaothong,
Samutprakarn, 10540 THAILAND.

Tel: 0 2315 4155-8 • Fax: 0 2315 4159

WWW.CHAREONTUT.COM